

SOLaTM

ingenico
aWorldlinebrand

Ingenico Desk/5000 Datasheet



Desk/5000

Speed up checkout at the counter,
even in the most demanding environments



- Provide a robust design for demanding situations
- Enable alternative payment methods
- Manage space constraints at the counter thanks to a seamless connection to PIN pads





The Desk/5000 covers the most demanding use cases at the merchant's counter. With the ability to connect to other POS devices – including the Desk/1000 series PIN pads for richer customer interactions – Desk/5000 is focused on payment in all forms.



• **Robust design for demanding environment**

The responsive keypad improves PIN entry combined with the advanced outer casing make the Desk/5000 very robust, to suit with the most demanding situations.

• **Optimized checkout with a PIN pad connection**

The compact Desk/1000 series can connect to Desk/5000 terminal – saving space on the worktop and speeding up the checkout.

• **Highest security**

The Desk/5000 is certified and fully compliant with the latest global and local PCI regulations. The Telium TETRA OS has been future-proofed with top-of-the-line cryptography software and Ingenico's world-class peer-to-peer encryption technology to keep data safe.

• **Optimal user-experience**


The terminal's intuitive user interface – including powerful multimedia capabilities and a large 3.5 inch color touchscreen – provides best-in-class experiences for customers.

• **Sustainable design and packaging**

Our state-of-the-art manufacturing techniques enhance the ability to recycle this terminal. Paper consumption has been reduced on the Desk/5000 thanks to new digital receipt solutions and digitized product documentation.

• **Compatible with Ingenico's suite of services**

Keeping the solutions connected, the Desk/5000 works in unison with Ingenico's supporting service platforms, meaning merchants will have access to business services such as estate management



| | | | |
|------------------------------|--|---|----------------------|
| Processor | <ul style="list-style-type: none"> Application & Crypto processor | <ul style="list-style-type: none"> Cortex A5 | ✓ |
| Memory | <ul style="list-style-type: none"> Internal External | <ul style="list-style-type: none"> 512 MB Flash, 512 MB RAM MicroSD up to 32GB | ✓ |
| OS | | <ul style="list-style-type: none"> Telium TETRA | ✓ |
| SAM | | <ul style="list-style-type: none"> 2 SAM | ✓ |
| Card readers | <ul style="list-style-type: none"> Magstripe Smart card Contactless | <ul style="list-style-type: none"> ISO 1/2/3, 500K lifespan EMV Level 1, 500K lifespan EMV Level 1 | ✓ |
| Display | <ul style="list-style-type: none"> Color | <ul style="list-style-type: none"> 3.5" backlit, HVGA (480x320) pixels | ✓ |
| Touchscreen | <ul style="list-style-type: none"> Resistive | | ✓ |
| Keypad | | <ul style="list-style-type: none"> 16 hardtop keys, raised marking, backlit | ✓ |
| Audio | <ul style="list-style-type: none"> Buzzer Speaker Audio Jack | <ul style="list-style-type: none"> Mono Stereo | ✓ |
| Video | <ul style="list-style-type: none"> Video accelerator | <ul style="list-style-type: none"> H264 codec | ✓ |
| Thermal printer | <ul style="list-style-type: none"> Speed in l/s Paper roll cage | <ul style="list-style-type: none"> 20 l/s 2 1/4" (58mm) width x 40mm | ✓ |
| Terminal connectivity | <ul style="list-style-type: none"> Wired | <ul style="list-style-type: none"> Dial-up MODEM Ethernet 10/100 base T | ✓ |
| Terminal connections | <ul style="list-style-type: none"> USB Power Supply | <ul style="list-style-type: none"> 1 USB Host 1 USB Slave Dedicated power Jack 1 RS232 | ✓ |
| Power supply | | <ul style="list-style-type: none"> 32W (8v – 4a) | ✓ |
| Terminal size | | <ul style="list-style-type: none"> 7.3x2.6x3.2x2.6" (187x82x68 mm) | ✓ |
| Weight | | <ul style="list-style-type: none"> 12 oz (340 g) | ✓ |
| Environment | <ul style="list-style-type: none"> Operating Temperature Storage Temperature Operating Humidity | <ul style="list-style-type: none"> 32°F to 104°F (0°C to +40°C) -4°F to 131°F (-20°C to +55°C) 85% non-condensing at 104°F (+40°C) | ✓ |
| Accessory | <ul style="list-style-type: none"> Magic Box Privacy shield Stylus Kit | <ul style="list-style-type: none"> 1xRS + 1xPower+1xEth.+1xLine In Field upgradable | Optional Optional |
| Security | | <ul style="list-style-type: none"> PCI PTS 5.x | ✓ |



www.ingenico.com

ingenico SOLA™